

230.090.000
starCASE SC 090



technical data

Material	ASA LURAN
Protection class	IP 66/EN 60529
Colour	Light grey RAL 7035
Certifications	GOST
Length	120 mm
Width	90 mm
Height	50 mm
Weight (g)	155 g
Country of manufacture	Germany
Customs tariff number	39269097

starCASE

ADVANCED PLASTIC ENCLOSURES MOULDED IN FLAME-RETARDANT ASA+PC

IP 66

starCASE is a truly multipurpose range of plastic enclosures moulded in flame-retardant ASA. These highly attractive and ergonomic housings are perfectly suitable for modern industrial electronics. The enclosures can be mounted on a wall, bulkhead, ceiling or machine – everything is possible.

Unique ROLEC design features include a recessed lid for fitting a membrane keypad, product label or front plate, hinged design covers which hide the lid screws and separate mounting channels, and lid retaining supports for holding the lid in place when the housing is open. The enclosures can be mounted without opening the lid which means your electronics remain protected at all times. Screw bosses are provided inside for fitting circuit boards, mounting plates, terminal rails etc. An optional lock prevents unauthorised access. Matching accessories and cable glands are also available.

We can supply starCASE enclosures fully customised to your requirements.

Enclosure sizes

8 sizes

Dimensions L x W x H

120 x 90 x 50mm to 280 x 170 x 60mm

Further information

Integrated recess for membrane keypads or front plates

Integrated lid support, polypropylene (PP)

Optional: Access safeguard by means of insert locks/sealing set

Full protective insulation in accordance with VDE 0100

Enclosure

ASA+PC, RAL 7035 light grey: 2° mould slope for casting ejection > internal circumference dimensions decrease by 2° towards enclosure base.

Snap-on design covers, captive, ASA LURAN S, RAL 7035 light grey

Special materials and colours on request

Flammability

UL 94 V-0 1.5 mm

Fastening

Separate screw channels outside of the enclosure interior. Enclosure fastened while lid closed

Internal mounting

Fastening option for self-grooving screws on the base of the enclosure and in the lid

Ingress protection
IP 66 / EN 60529

Gasket
Silicone moulded seal, temperature range: -50°C to +140°C


Lid screws
Stainless steel 1.4567, captive

Customising
Learn more about our full customising service for installation-ready enclosures


Enclosure series starCASE

Type: SC 090

Material-No.: 230.090.000



* Please note: Mould slope for casting ejection, dimensions in the amount of the bottom!

Enclosure material	ABS, UL 94 V-0 1,5mm, RAL 7035, light grey		Weight	155 g
Lid screws	4x stainless steel 1.4567 (V2A), captive		Assembly screws	4x KBL Ø3x8,5, galvanized steel
Gasket	1x moulded gasket, silicone, black		Lid supports	2x Polypropylen (PP), white
Ingress protection	IP66 EN 60529		Tolerance	DIN ISO 16901-130 (outside dimensions ±0,5mm)